

O.T. TABLES, LIGHTS & VETERINARY INSTRUMENTS



MODEL: XL-666 VET

Small Animal Examination Table

Heavy Duty sturdy design with 20 gauge SS. Durable & easy to clean.
Large exam surface (150 x 60 cms including Flap 2" X 2")
Strong tubular pipe frame of Ø 3 cm.
Table top drainage facility in center
Height can be adjusted manually
Equipped with instrument tray on the head side with the facility to move.
Facilitated with adjustable hobble pin to tie the animal
IV stand for firmly fixing on all sides of tables
Thick steering rings made of Stainless Steel of 3 cm diameter.
Facility to hold Stainless Steel Tray
3" heavy duty locking castors hold the table securely in place for exams and roll easily even on uneven floors.



MODEL: XL-2000 VET

Small Animal O.T. Table With V-Cut & Central Drainage System

Overall length: 60"
Width over side railing: 22"
Height: 42" Max. & Min: 28"
Lift: 14 inch.
Load bearing capacity: 150 Kgs.
Rotation: 360° around its axis.
Table Top: High Grade SS (304 Satin Finish) 18 gauge
Special Features
Central Drainage System with feed silica flexible pipe.
Hydraulic lift with pumping & rubber top paddle for lift and pressing down to glide table to lowest position.
V-Cut position



Model: XL-777 Vet CV

Small Animal O.T. Table (Economical)

Overall length: 60"
Width over side railing: 22"
Height: 42" Max. & Min: 30"
Lift: 10/12 inch.
Load bearing capacity: 150 Kgs.
Auto floor locks for any position and table on heavy duty castors.
Section: 1/3/5 section 14mm thickness (3 options available)
Rotation: 360° around its axis.
Table Top: High Grade SS (304 Satin Finish) 18 gauge
Special Features
Table has one end Tilt mechanism from horizontal to near vertical with lock at selected angle.
Hydraulic lift with pumping & rubber top paddle for lift and pressing down to glide table to lowest position.



MODEL: XL-777 VET-E

SMALL ANIMAL O.T. TABLE

Trendelenburg & Reverse Trendelenburg 35°
Lateral Tilt Both side 22°
Head Section Translucent detachable/ Interchangeable with head section 90° up (Optional in 3 Section Table)
Leg Section 90° down (Manual)
Flex/Reflex & Kidney Bridge 30°/220°
18 gauge (304) with 360° rotation of table top
Overall length 60"
Width over side railing 22"
Height 42" Max. & Min 30"
Lift 10/12 inch.
Load bearing capacity 150 Kgs.
Auto floor locks on any position and table on heavy duty castors.



MODEL: XL-777 VET



MODEL: HAICO FOR HORSES

LARGE ANIMAL EQUINE TABLE

The main frame is made of structural steel.
The padded top has a total lateral surface area of 46x84 in. (117x213.4cm).
The center bed of the table top is 18 in. (45.7cm) wide by 84 in. (213.4cm) long.
The corner hinged wings are 12 in. (30.5cm) wide by 18 in. (45.7cm) long and the center hinged wings are 12 in. (30.5cm) wide by 36 in. (91.4cm) long.
Both center wings are removable.
The top is padded with one layer of 1½ in. (3.8cm) ensolite and one layer of 18 oz. vinyl coated nylon fabric.
The padded surface is adhered to a wood support that is fastened to the steel frame of the respective wing.
The four corner dorsal wings are hinged on a rod bar and can slide up against the center wing or can slide to provide the full 84 in. (213.4cm) of support.
All wings have five different tilt positions via a manual prop bar

O.T. Light (Mobile)

Dome: 1 no., Dome Diameter: 500 mm (nominal)
Spring arm stroke: 750 mm +/-50 mm
Field size: 150-200 mm, Action radius: 160° (Nominal)
Light output: 1, 30,000 lux (max.)
Color temperature: 4200 +/- 300°K
Halogen bulb: 4 nos. 12V, 50 W each/24V 70W
Filter: Glass for Heat Absorbing
Low voltage unit with CVT: 1 no.
Height Adjustment of Dome: 36°
Mobile: Heavy duty Castors
Outer Finish: Epoxy Coated with SS Arm and Base
Sterilizable Autoclavable Handle
Inbuilt Battery Backup (2 hrs.)



MODEL: SSML-4 VET

O.T. Light (Ceiling Suspended)

Digital Control Panel with following systems:
On-off micro switch with Focus control
Intensity control micro system
Time Delay circuit for the protection of bulb against sudden high voltage
Higher depth of field ensures proper light without adjustment of focus even at different heights
The operating lamps reduce shadows by throwing multiple beams using a multi source balanced optical system with honeycomb diffuser
The advanced optics and halogen lamp produce the optimum color temperature for highlighting tissue with the minimum of eye fatigue
Special mirror coating that reflects colder light but allows hot infrared light to go up



MODEL: SSCL-7 VET

Other Options : Imported LED O.T. Lights

MAGNETIC THERAPY SYSTEM FOR HORSES

Price on Request



Champion Body Blanket

Our champion body blanket with 25 coils - especially for local therapy and enhancement of the performance of horses.
This inner life may be removed for washing the coating.
Massage function with 5 programs, 4 and 5 zones intensities.



Cervical collar therapy

Cervical collar therapy for local treatment.
Of course, with zipper for washing the coating, or for removing the coils.



Gaiter (60 / 30 cm)

Gaiter large 60 / 30 cm length to local therapy.
60 /30 cm tall gaiter
With zipper for washing the coating, or for removing the coils.



Hind Leg

Hinterbeingamaschen for horses
Gaiter for rear leg of the horse to local therapy
Hinterbeingamache zip
Of course, with zipper for washing the coating, or for taking out the bobbin

Exclusive Distribution of M/s Magnetovital in India by
S.S. Medical Systems (I) Pvt. Ltd.



Uttarakhand

09639060683

Delhi

08090075719

Lucknow

09792444111

Mumbai

09452010000

Bangalore

08948122222

Chennai

09415937232

24x7 HELPLINE
09838202281

Overseas



Dubai Office:
P.O. Box-922,
Dubai,
U.A.E.
Ph: # 0097-1504967256



U.S.A. Office
287 Stillwater Drive,
Yuba City,
CA 95691
Ph: # 415 407 5108



U.K.
Room No. 004.4, Central Village,
Black-A, Woodhouse Lane,
Leeds, LS2, 3AB
Ph: # 0044-7785536498

Our Veterinary Equipments

VET. DIGITAL RADIOGRAPHY

VET. C-ARM

VET. OSTEOPOROSIS

VET. ULTRASOUND SCANNERS

VET. COLOR DOPPLERS

VET. MONITORS

VET. ECG MACHINES

ANESTHESIA (SMALL & LARGE ANIMALS)

O.T. TABLES (SMALL & LARGE ANIMALS)

O.T. LIGHTS

VET. INFUSION PUMPS

VET. PATHOLOGY EQUIPMENTS

VET. PRE-MATURE INCUBATOR

VET. OTOSCOPE

VET. PREGNANCY KIT

MASTITIS DETECTOR

VET. VENTILATOR

VET. DENTAL IMAGING

VET. ELECTRO-SURGICAL UNIT

VET. SURGICAL INSTRUMENTS

MAGNETIC THERAPY FOR HORSES

LIST OF VETERINARY INSTRUMENTS			
S.No.	Name of Instrument	Qty.	Remarks
1.	A. I. Gun German Type, French, Min French Type	1 No. Each	
2.	Artificial Vagina With Metal Valve 8" 10", 12", 14"	1 No. Each	
3.	Tooth Cutter Molar Danish Pattern	1 No.	
4.	Pipette Container Alum. Sheet 11/4"X20", 2"X20"	1 No.	
5.	Vaginoscope Coldite Brass C.P. in Box	1 No.	
6.	A.I. Kit In Metal Case Containing 15 Items	1 No.	
7.	Trocar & Cannula Heavy Metal Handle, Wooden Handle	1 No. Each	
8.	Bull Holder Aluminium With Thumb Spring	1 No.	
9.	Burdizzo Castrators B.C.P. 9", 19"	1 No. Each	
10.	Tennaculum Forceps 10"	1 No.	

* This is a partial list our veterinary instruments, in case you need more items, please feel free to contact us.

Mfd. & Mktd. in India by :

S.S. MEDICAL SYSTEMS (I) PVT. LTD.

Manufacturing License No.: 05110000488 | Class-1 Local Supplier

Manufacturing Unit : #F2, Bhimtal Industrial Estate, Bhimtal, Distt. Nainital, Uttarakhand-263136 | Ph.: 05942 248138 | Mob.: 09839022234

National Sales Office: #707, Ansal Bhawan, #16, K.G. Marg, Barakhamba, New Delhi-110001 | Ph.: 011-41060439 | Mob.: 08090075719

• Delhi • Mumbai • Lucknow • Bhimtal • Kolkata • Chennai • Bangalore



WE CAN SERVICE / REPAIR ANY MAKE !!

- X-RAY (HF & 2 Pulse)
- ULTRASOUND & COLOR DOPPLER
- VET. MONITORS
- ECG MACHINES
- O.T. TABLES
- O.T. LIGHTS
- INFUSION PUMPS
- VET. HOSPITAL FURNITURES

All India Service Centres available for prompt services at:

Due to continuous research & development, images shown in this catalogue is only for depiction, however actual product may slightly differ from the images shown here.

Product Catalogue (Veterinary Medical Equipments)

2022-2023




Our International Representation



Our Range of Veterinary Products



MODEL: ASR-9150-C VET



MODEL: INNO-VET-DR



MODEL: SS-C VET



Mini Omni (BeamMed)



Model : DIGI 600 MW VET



Model : DIGI 600 HYPER 4M VET



Model : DIGI 600 M PRO VET

Digital Radiography

Powerful Image Processing Software
Excellent Image Quality with 50KW HF Generator
CCD / Flat Panel Detector 17"x17" & 4kx4k 16 million pixel
Photographic System
Automatic exposure control system (AEC)
Hi-Frequency X-Ray Generator
Dedicated Vet. Software for Radiology Parameters i.e. mA, kV, mAS for Canine, Bovine, Feline, Equine etc.
Reconstruction software with dedicated computer and dry film camera.

VETERINARY PORTABLE DR

The **INNO-VET DR** solutions combine the advantages of a DR system with a great deal of versatility.
The **INNO-VET DR** solution is the perfect choice if you value mobility for field work, easy and efficient workflow and high quality x-ray images - all at an affordable price.
DETECTOR
Detecting area 20 x 26 cm (8 x 10")
Light weight: 2.9 kg
Direct-Conversion Technology, highest image quality
Remote control, protective cover and spacer

Veterinary C-ARM

Combination of 6" CCD camera with a High definition Image-Intensifier and newly developed digital image processor presents high definition image.
Design provides ADC (Automatic Design Control) for hands-free imaging. Choice of image processing, Digital Image Rotation, Contrast Stretching, Averaging.
Memory with 25 images has low noise level
Mechanical design to provide enhanced maneuverability with ease of C-Arm & other movements.
Ergonomically designed handles, levers and trolleys.
Aluminum reverse "C" provides complete balancing with sterilized draping during surgery.
Available in 9" & HF modules

Vet Osteoporosis

Sunlight MiniOmni™ is an ultra-small device that can bring a huge benefit to to primary bulk screening for osteoporosis diagnosis and monitoring.
Highly affordable and easy to use.
It delivers accurate bone density measurements.
Sunlight MiniOmni enables early assessment of osteoporosis – without X-Rays.
Light weight and compact with Convenient carry case.
USB connectivity; Windows-based. Works with Windows® XP/7 PCs and laptops.
No disposables, with near-zero cost of operation.
WHO-compliant T-score and Z-score results.
Easy to understand, graphical measurement report created within minutes.
Radiation-free & Non-invasive.
Precise measurements - a unique multi-site measurement (optional).
4 ethnical reference databases for animals (optional).

Hand Held Wrist Ultrasound Scanner

5.7" high resolution color TFT LCD monitor
Scanning modes: B, 2B, 4B, B/M, M
Full field image with 8 levels depth adjustment
Dynamic range: 27 – 90 dB, visual adjustment, Local zooming function
100 frames image storage with wrist strapper, Cineloop: 256 frames
Supports large capacity USB disk and mouse
Eight kinds of internal pseudo color display
1.1 Kg, Backpack integration design convenient for veterinary and farm use

Portable B&W Ultrasound Scanner

4.5Kg net weight for easier carrying. AC and battery power supply
256 gray scales 10.4" LCD & Hundreds of cine loop
Multi-frequency probes (Optional)
Software upgradeable
Video and VGA output, 2 USB ports, Car charger
6-Segment TGC and Overall Gain with partial zoom and picture display
Measurement of Distance Area/perimeter, volume (ellipse method) Angle
Heart Rate, Time EF slope, Fetal Age, Weight and EDCB
Software for Sheep, Swine, Bovine, Equine, Canine, Feline & llama
Option of Probes, Accessories etc is available on request.
Option: Cost of Probes & Accessories shall be extra.

Portable B&W Ultrasound Scanner

Dual power supply system (2 hrs. battery backup)
Extensive analytical Applied Software Package
Compact 8 Kg. weight with carry bag
Friendly fully Digital Platform
Internet/DICOM based upgradeable
12.1" TFT LCD monitor, 500 frames CINE loop
Two transducer connectors
Electronic Convex transducer (2.0/3.0/4.0/5.0/6.0MHz)
Veterinary application software for canine, feline, equine, bovine and ovine
Option: Cost of Probes & Accessories shall be extra.



Model : DIGI 600 MBZ VET



Model : DIGI 1100 CD-E VET



Model : DIGI 1100 CD VET



Model : SSD 6000 CD VET



MODEL: SONO-OX-PL VET



Model: MAX-E VET



Channels: 1/3/12 Options



Model: MAX-69 VET

Portable B&W Ultrasound Scanner

12" LCD Monitor
2 Transducer Connector
4 USB Ports, 1VGA, 1 RS232
2 Transducer Holders, 1 Coupling Gel Holder
Built-in Hard Disc (250GB) and battery
365 frames Cine Loop and Snapshot Functions
Calculation & Measurement Software for veterinary applications
Electronic Convex Transducer (2.5/3.5/5.0 MHz)
Option: Cost of Probes & Accessories shall be extra.

Portable Color Doppler

Main Unit, 12.1" LED monitor, Backlit Control Panel with dedicated Equine, Bovine software & vet probes.
2 Probe connectors, Hard disk (160 GB), DVD - RW, 2 USB ports, Unique Gel holder.
Built-in Lithium battery for 2 hours continuous work
Imaging Modes: B, 2B, 4B, B/M, B/BC, CFM, PW, HPRF, Power Doppler, Chroma B/M/PW/CW
Multi-Beam Forming (mBeam), Beam Forming Optimization (BFO)
Tissue Harmonic Imaging on all probes
Speckle Resistance (eClear) / Phased Inversion Harmonic Compound Imaging(EHCl)
Measurement packages for Canine, Bovine, Feline, Equine and Ovine.
Electronic Convex/Linear/Micro-Convex Phased Array, wideband, multifrequency probes.
Option: Cost of Probes & Accessories shall be extra.

Portable Color Doppler

Main Unit 15" LCD, 2 probe connectors with dedicated Equine, Bovine software & vet probes.
Large capacity memory, 2 USB ports, Video Out, TV Out, LAN port, VGA Out
Imaging Modes: B, 2B, 4B, B/M, CFM, B/BC, PW, HPRF, CW, PD, Directional PD, Instant Triplex, Duplex, Trapezoidal imaging, Panoramic imaging etc.
Double Phase Digital Beam Forming Technology.
Tissue Harmonic Imaging on all probes
Multiple Compound Imaging
Measurement packages for Canine, Bovine, Feline, Equine and Ovine.
Electronic Convex/Linear/Micro-Convex Phased Array, wideband, multifrequency probes.
Option: Cost of Probes & Accessories shall be extra.

TROLLEY MOUNTED COLOR DOPPLER

17-inch high definition LCD/TFT monitor
A full range of cardiovascular transducers
Attachable, phased array, high frequency phased array, 15MHz linear, etc.
Up to 512 HD transducers with frequency range from 1.9 to 15MHz.
Integrated with state-of-the-art technologies, like micro-scan imaging technology, multiple-beam processing, automatic flow volume analysis, 4D imaging technology, etc
Steer M mode, Color Flow Mapping CFM, Continues Wave Doppler CW, HPRF, Tissue Doppler Imaging TDI (optional), Panoramic image (optional), etc.
Full pet database solutions: DICOM3.0 (optional), AVI/JPG, USB2.0, HDD, DVD, PDF report, etc.
Option: Cost of Probes & Accessories shall be extra.

Vet. Pulse Oximeter

Compact, light easy for carrying and handling.
Parameters: SpO2 and Pulse rate
Easy to adjust LCD display, brightness to optimize viewing.
Two selecting working modes: spot-check and monitor.
Visual and audible alarm signals.
Trend data storage time up to 120 hours.
Trend data can be transferred to PC for printing, analysis and viewing.
Functional of management data analysis.
Veterinary SpO2 sensor.
Suitable for cats, dogs and horses.

VET. ANESTHETIC MONITOR

ECG trace & SpO2 Plethysmograph on high-resolution 7" bright LCD display.
In-built rechargeable battery.
Interface facility with central monitoring system.
Portable & easy to carry.
Parameters- ECG, SpO2.
Suitable for veterinary purpose with suitable accessories.

ECG Machines

ECG trace & SpO2 Plethysmograph on high-resolution LCD display.
In-built rechargeable battery.
Interface facility with central monitoring system.
Portable & easy to carry.
Parameters- ECG, SpO2.
Suitable for veterinary purpose with suitable accessories.

Vet. Modular Monitor

12.1" Color TFT display with 7 waveforms
Standard Parameter: ECG, RESP, TEMP, SpO2/Pulse Rate, NIBP
Optional Parameter: Anesthetic Gas.
Complete built-in module design ensures stable and reliable performance
Store & review 168 hours trend data and trend maps
Built-in recorder (optional) supports real-time recording, trigger printout by alarm.
Applications from small to large animals.
Special vet. Probes available for Dogs, Cats, Horses & Bovine.



Model: AP-12 VET



Model: APV-12 VET



Model: SS-9215 VET-S



Model: SS-9215 VET-L



Model: SS-INC-150 VET



MODEL: SS-01 VET



MODEL: SS-01 VET



MODEL: SS-3000 VET



MODEL: SS-3000 VET

Syringe Infusion Pump

Continuous Micro-infusion in ICU and CCU.
Injections of hormones & Continuous injection of anesthetics.
Injection of oxytocics / anticoagulants
2 Operation Mode with 7 Flow rate Units for options.
7 audible and flashing alarms with wide range flow rate.
Intelligent LCD display & Data sharing with PC.

Volumetric Infusion Pump

Tube heating function with Dual-CPU monitoring function
Setting the system time
Body-weight mode conversion
3-level occlusion alarm limits setting
1500 history records
Detection of drip sensor
Wireless communication function
Smart pulsation compensation function

Small Animal Endoscope

High definition image: adapt the 440K pixels, high resolution CCD (color charge-coupled device). It can capture high quality images
Wider field of view technology can provide excellent and detailed images
A 180° up /180° down angulation makes it easier to observation
5-100mm depth of view provides precise observation ability for both close and far objects
It is more convenient that Vetscope can be connected with LCD, to offer maximum comfort during examination
It is easier to operate that a wide range of instruments can be used with the 3.2 mm diameter channel

Large Animal Endoscope

Flexible endoscopy of 2.5 meters for large animal with front view (Gastroscope) and approx 9 mm aperture.
Digital video camera with C-mount, light source and High-Low insufflator.
Unit mounted on endoscopic cart with two medical grade monitors minimum 17 inch each.
Televise endoscopic images for diagnosis / treatment / photo video document in conjunction with endoscope, light source with video accessories.
Light intensity with automatic adjustment, auto wide balance and color adjustment.
The camera unit is single chip unit must be usable with rigid or (with adapter) flexible scope.

Vet. Pre-Mature Incubator

The controller is based on Micro computerized system.
Large bright displays are easy to monitor and for viewing from a distance.
Digital display system provided to measure the Infant temperature.
Air temperature and to set the required temperature.
Feather touch keys provided for easy operation.
Bar graph LED system provided to indicate the heater output.
Height: 1425 mm, Depth: 585 mm, Width: 945 mm
Working level from the ground : 900 mm
Baby tray tilt angle on either side : +/-8° max
Weight : 60 kg (Approx)
Castors : 125 mm with 2 brake wheels and 2 non-brake wheels
Baby probe / Air probe is made of highly sensitive sensor and interchangeable, field calibrations taken care of by veterinary software.
The probe is made up of silicon sheathed cable, which allows easy cleaning.

Vet. Pregnancy Test Instrument

SS-01 Vet instrument is also veterinary ultrasound scanner.
It's for pregnancy test of swine and goat with high efficiency and convenience, exquisite outline, dust-proof and water-proof.
It's perfect for outdoor, lawn, complicated environment, etc.
Professional pregnancy test for swine & goat.
Smart size, easy to carry
Battery is easy to purchase and replacement
Water-proof
With different feedback through sound and light, easy operation
Size: 180X50X50 mm (LXWXH)

Mastitis Detector

The diagnosis at the earliest stage of the disease-the way to produce high quality milk
Fore-stripping and monitoring the udder condition at once
The assessment of the udder quarter condition based on the electrical resistance of milk
The durable and water proof case allows you to work in the toughest conditions
One of the biggest problem, which often occurs in milk cows breeding is the udder inflammation - MASTITIS
The state of subclinical inflammation called Mastitis subclinical is very costly. However, milk in this state does not show changes in taste and appearance and the udder has no visible lesions. Milk from diseased quarters, has poor quality and the productivity of this quarter is limited.

Vet. Otoscope

Innovative, compact battery handle in a high-quality, modern design.
Ophthalmoscope in a unique, compact design with outstanding optics for even the smallest dimensions.
High-quality handle: Chrome-finish upper section / refined plastic: Shockproof, sturdy, non-slip.
Oval, compact, stylish shape: Lies ergonomically in the hand.
Attachment clip with integrated ON / OFF switch.
Enhanced XHL Xenon Halogen Technology.
5 different apertures: A full-function instrument incl. fixation star.
Range of lenses:-20 to +20 D.
+3 D lens attachment: Aids accommodation and magnifies image.
Finger-tip pressure releases the used blade: No need to touch the blade after use.



SS 250 D-VET (250 Watts)



MODEL: SAAM-7 VET



MODEL: FABIA



MODEL: SS-40 VET

PATHOLOGY EQUIPMENTS



MODEL: SS-168 VET



MODEL: SS-6800 VET



INTRASKAN digi RVG

Vet. Electrosurgical Unit (Cautery)

The SS-250 D-VET is a micro controller based electrosurgical unit that consist all features to deliver excellent performance of modern surgery and provide efficient cutting and coagulation effect.
It adapts Tissue response circuit for greater advantages.
Reduces RF distortion in the OT equipments due to noiseless performance.
Push button switches for mode selection and mode identified by different LED indicators analogue control for power output.
Equipped with vet. patient plate monitor.
Independent activation of monopolar and bipolar output, hand & foot switch activation of power.

Small Animal Anesthesia

A microprocessor based, electronic, time cycled, pressure limited, anesthesia ventilator
Bellows Orientation Inverted volume 18 Litre
Optional Pediatric Bellows: 200 - 2.2 Liters with Small Animal Absorber Circuit
Controls Inspiratory Time: 1 - 3 seconds, Inspiratory Flow 10-650 LPM, Inspiratory Pressure 10 - 70 cm H
Rate : 2 - 80 BPM Pneumatic Manual Push Button Yes For Inspiration
LED Display: Inspiratory Time Rate (BPM)
Alarms and Alerts Failure to Cycle: Visual-Audible System Failure, Visual-Audible Safety System Overpressure Governor 80cm H2O (adjustable)
Gas Scavenge: 19mm port
Absorber Valve: For Soda Lime 6 Liters
30" width x 24" depth x 57" tall (76 cm width x 60 cm depth x 144 cm tall)

LARGE ANIMAL ANESTHESIA

Two Gases Rota Meter O2 & N2O with Epoxy Coated Rust Proof Heavy Duty Frame.
Oxygen Flowmeter Range 100cc/min. to 10 litres/min. Nitrous Oxide Flowmeter range, 200cc/min to 10 litres/min.
Built-in parking space for two additional Vaporizers Isoflurane, Halothane etc
Circle Absorber leak free with transparent canister
Table Top made of Stainless Steel.
Top Tray provided at eye level for keeping Monitoring Equipments.
Two Self Sealing quick Coupling type gas outlet One each for O2 N2O at the rear side for 2 central pipe line connection with 5 ltr./min. flow rate.
Separate Oxygen Flow meter for independent Oxygen supply.
Saline stand locate at above right side of Trolley. Provision to fit Ventilator/IPPV.
Extended Platform at rear to accommodate Two 'B' Type Cylinders with total 4 cylinder capacity of 600 ltrs.
Fitted with four large diameter color coded Gadges two each for O2 & N2O.
Two color coded extra gauges to show Pipeline Pressure O2 & N2O each.
Option of Imported Vaporizers for Halothane / Isoflurane etc available.

VET. VENTILATOR

Micro-processor controlled and electrically driven ventilator
Modes: CMV, ASSIST & SIMV
Portable & Easy to operate on small & medium size 300 Kg animals
Compatible with anesthesia machine
Standalone-no need of driving gas
Suitable for use in ambulance
Ultra low operating cost & Low maintenance
Excellent for use in operation theatre & ICU

Vet. Biochemistry Analyzer

Professional design assures convenient operation and accurate measurement
Friendly man-machine conversation interface based on built-in Windows.CE.NET
Touch screen, external keyboard, mouse and printer supported
Test methods include End-point, Two point, kinetic, reagent blank, sample blank immunity nephelometry, and multicate selectable calibration methods, such as multi-standards, linear or non-linear calibration curves etc
Real-time display absorbance curve
Prolonged light source and filter life by intelligent light source protection
8 species of animals available and 8 additional species for user to customize
Application: veterinary clinics, pet hospitals or animal research institutions, etc

Vet. Hematology Analyzer

Methodology: Electrical resistance for counting, hemoglobin cyanide method and SFT method for hemoglobin
Parameter: 3-part differentiation of WBC 20 parameters + 3 color histograms (WBC/RBC/PLT)
Sample volumes: Venous Mode: 9.6 µL, Pre-diluted Mode: 20 µL
Operation mode: Windows operation system with keyboard & mouse input
Throughput: ≥ 40 samples/hour, 24 hours work with auto standby
Storage: 12,000 sample results inclusive of the histograms
Species of animals: Dogs, Cats, Horses, Cattle, Goats, Monkeys, Mice, Pigs, Chooks, Rabbits and four user defined modes

VET. DENTAL IMAGING

Patient registration with photo
Patient browser, Scanned tooth display
Measurement tools, Sensor setting
Display setup, Image Zoom, Flip, Rotate, Measure
ROI Study
Image fusing with Laptop display